

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/014806 A2

- (51) International Patent Classification⁷: C02F 1/467 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number: PCT/IL2003/000662
- (22) International Filing Date: 10 August 2003 (10.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 151181 11 August 2002 (11.08.2002) IL
- (71) Applicant and
(72) Inventor: ELGRESSY, Gabby [IL/IL]; 16 Shechterman St., 42379 Netanya (IL).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report
- (74) Agent: FRIEDMAN, Mark, M.; Dr. Mark Friedman Ltd., 7 Haomanim Street, 67897 Tel Aviv (IL).

[Continued on next page]

(54) Title: A COMBINED ELECTROCHEMICAL SYSTEM FOR SCALE TREATMENT AND ERADICATING LEGIONELLA PNEUMOPHILA BACTERIA IN WATER SUPPLY SYSTEMS



(57) Abstract: A combined electrochemical system for scale treatment and eradicating bacteria in water supply systems having: (a) a first electro-chemical cell including: (i) a first metallic tank for receiving a water supply and forming a cathode of the first electro-chemical cell, and (ii) a first anode, disposed within the first tank; (b) a second electro-chemical cell including: (i) a second metallic tank for receiving an effluent from the first tank and forming a cathode of the second electro-chemical cell, and (ii) a second anode, disposed within the second tank; and (c) a DC electrical supply source operatively connected to the first and the second cells, wherein the first electro-chemical cell is operative for trapping bacteria in a colloid-like structure, and the second electro-chemical cell is operative for producing a pH above 12 near the walls of the second tank, so as to form a bacteria-containing precipitate on the walls of the second tank, thereby removing the bacteria from the water supply.